



## Castrol ATF Dex III

Automatic Transmission Fluid

### Description

Castrol ATF Dex III is designed for use in GM automatic transmissions pre 2005 and in Ford automatic transmission built between 1983 and 1996 where Dexron® (II or III) or Mercon performance is required. Also suitable as Power Steering Fluid.

NB: Should not be used where Dexron® VI, Mercon® V or Mercon® SP are required

### Advantages

- Enhanced friction durability prolongs transmission life and promotes smooth shifting.

### Typical Characteristics

Name	Method	Units	ATF Dex III
Density @ 15C, Relative	ASTM D4052	g/ml	0.851
Colour	ASTM D1500	-	Red
Viscosity, Kinematic 40C	ASTM D445	mm <sup>2</sup> /s	35
Viscosity, Kinematic 100C	ASTM D445	mm <sup>2</sup> /s	7.4
Viscosity Index	ASTM D2270	None	185
Viscosity, Brookfield @ -40C (75W)	ASTM D2983	mPa.s (cP)	16200
Pour Point	ASTM D97	°C	-51
Flash Point, PMCC	ASTM D93	°C	200

### Product Performance Claims

Meets Dexron® IIIH, Mercon®  
Suitable as Power steering fluid

## Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol ATF Dex III  
19 Mar 2015

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

[www.castrol.com](http://www.castrol.com)